

SPECIFICATION AMENDMENTS

None

CLAIM AMENDMENTS

Claim Amendment Summary

Pending

- Before this Amendment: Claims 21, 23, 25-30.
- After this Amendment: Claims 21, 23, 25, 27-30.

Canceled: Claim 26.

Amended: Claims 1, 4-8, 10, 12-15, 17, 21, 23 and 27-29.

New claims: None

Claims:

- 1. (Currently Amended)** An end host comprising:
- a memory including:
- executable instructions;
 - storage for respective identifiers for respective peers of the end host
- in a peer-to-peer system, wherein the storage comprises:
- a multilevel routing table cache (MRTC),
 - each level in the MRTC ~~has~~ includes a maximum number of entries,
 - each level in the MRTC represents a segment of a number space corresponding to an identifier of the end host,
 - the top level of the MRTC spans the entire number space,
 - each successively lower level ~~contains~~ comprises successively smaller spans,
 - each said span in a level below the top level is a smaller segment than the entire number space,
 - each said span is clustered around one said identifier of a corresponding said peer, and
 - the relative proximity between the peers corresponds to the respective identifiers ~~thereof~~; [[and]]

an array for each said peer of the end host, wherein:

each said array includes one ~~[[of]]~~or more entries; and

each said entry:

corresponds to one neighbor peer of one peer of the end host

(NPOP); and

includes an identifier for the NPOP; and

a processor for executing the executable instructions which, when executed, ~~interacts~~ cause the processor to interact with the end host as a peer in a peer-to-peer fashion in the peer-to-peer system, the interacting comprising:

when a message is ~~to be~~ sent from the end host to a destination, said peer having an identifier not found in the MRTC[[:]], forming a message for a destination ~~said~~ peer for which the identifier thereof is not found in the MRTC, wherein the message includes the identifier of the destination ~~said~~ peer; and

addressing the message to an intermediate said peer for which the identifier thereof[[:]] is in the memory[[:]] and where the intermediate said peer has an address which is the proximally closest to the identifier of the destination said peer.

2. (Canceled)

3. (Canceled)

4. (Currently Amended) The end host as defined in Claim 1, wherein the proximally closest ~~said~~ identifier of the intermediate said peer is found in a portion of the memory selected from the group consisting of:

one said entry in one said array; and
the MRTC.

5. (Currently Amended) The end host as defined in Claim 1, wherein:

a message ~~can be~~is delivered to a destination said peer from the end host by transmission via a number of said peers, wherein the number of said peers being not~~that is not~~ more than $O(\log_k N)$ ~~[[in]]~~ on average over time;

k is ~~the~~ a factor by which ~~the~~ spans of each said successively lower level is successively smaller; and

N is ~~the~~ a number of said identifiers in an identifier naming space for the MRTC.

6. (Currently Amended) The end host as defined in Claim 1, wherein the interaction of the end host as a peer in peer-to-peer fashion in the peer-to-

peer system comprises forming a message for delivery to a destination said peer via the one or more neighbor peers thereof said destination said peer.

7. (Currently Amended) The end host as defined in Claim 1, wherein the interaction of the end host as a peer in peer-to-peer fashion in the peer-to-peer system comprises[[:]] addressing a message for transmission to each said NPOP of the peer to which the end host is unable to communicate for further transmission [[therefrom]] to the peer to which the end host is unable to communicate.

8. (Currently Amended) The end host as defined in Claim 7, wherein the message includes a new IP address of the end host when the IP address of the end host ~~has~~change[[d]]s.

9. (Original) The end host as defined in Claim 1, wherein the interaction of the end host as a peer in peer-to-peer fashion in the peer-to-peer system comprises registering one said identifier for the end host with each of the respective peers of the end host in the peer-to-peer system.

10. (Currently Amended) The end host as defined in Claim 1, wherein the interaction of the end host as a peer in peer-to-peer fashion in the peer-to-peer system comprises:

establishing a communication connection between the end host and one said peer of the end host;

losing the established communication connection for a predetermined time threshold;

receiving a message from the one said peer of the end host ~~containing,~~ wherein the message includes a new IP address of the one said peer; and

resuming, using the new IP address, the communication connection between the end host and one said peer of the end host.

11. (Original) The end host as defined in Claim 10, wherein the message is received via one said NPOP.

12. (Currently Amended) The end host as defined in Claim 1, wherein relative proximity between the peers in the peer-to-peer system is a function of the proximity of the respective identifiers ~~thereof~~ of the peers.

13. (Currently Amended) The end host as defined in Claim 1, wherein:

each said identifier of each said peer is a numerical expression; and
relative proximity between the peers in the peer-to-peer system corresponds to numerical proximity of the respective identifiers ~~thereof~~of the peers.

14. (Currently Amended) The end host as defined in Claim 1, wherein:

each said array is a neighbor hint table (NHT); and

each said identifier for the NPOP comprises:

an IP address of the respective said NPOP;

a port number of the respective said NPOP; and

an ID generated from a public key of the respective said NPOP,
wherein relative proximity between the NPOPs is a function of the proximity of the respective identifiers ~~thereof~~of the peers.

15. (Currently Amended) The end host as defined in Claim 1, wherein each said identifier of each said peer comprises:

an IP address of the peer; and

an ID generated from a public key of the peer, wherein relative proximity between the peer and other said peers in the peer-to-peer system is a function of the proximity of the respective identifiers ~~thereof~~ of the peers.

16. (Original) The end host as defined in Claim 1, wherein the entries in each said array are ordered according to a priority of the NPOP selected from the group consisting of:

available bandwidth of the NPOP;
proximity of the NPOP to the corresponding said peer of the end host;
degree of trust between the NPOP and the corresponding said peer of the end host;
probability that the IP address of the NPOP will change; and
a combination of the foregoing.

17. (Currently Amended) The end host as defined in Claim 1, wherein the executable instructions further comprise an architecture that includes:

logic for a kernel layer ~~that has,~~ wherein the logic for the kernel layer comprises:

an internet protocol (IP) layer ~~having~~comprising an end-to-end mobility module for end communications between the end host and another end host in the peer to peer system; and

a transport layer on the IP layer for communications across interconnected networks of the peer-to-peer system; and

logic for an application layer on the kernel layer and ~~having~~wherein the logic for the application layer comprises:

a name resolution module for~~[[:]]~~ resolving ~~[[any]]~~ said identifier for a respective said peer in the peer-to-peer system to IP address~~[[;]]~~, and storing the identifier of the respective said peers of the end host in the storage; and

a notification module ~~[[on]]~~of the name resolution module for~~[[:]]~~ storing the identifier for each said NPOP in each said entry in each said array.

18. (Original) The end host as defined in Claim 17, wherein the transport layer on the IP layer is a TCP UDP layer.

19. (Original) The end host as defined in Claim 1, wherein each said peer in the peer-to-peer system is selected from the group consisting of:

a cellular telephone;

a computing device having a wired connection to the peer to peer system;
and

a computing device having a wireless connection to the peer to peer system.

20. (Original) The end host as defined in Claim 1, wherein the interaction of the end host as a peer in peer-to-peer fashion in the peer-to-peer system comprises:

receiving updates to the identifier for the NPOP for each entry in each array; and

sending an updated IP address for the end host to each peer of the end host.

21. (Currently Amended) A peer to peer system comprising first and second means for interacting as respective peers in a peer-to-peer fashion in a peer-to-peer system, wherein each said first and second means respectively [[has]]comprises:

a processing means for interacting in the peer-to-peer system;

one or more close peers in the peer-to-peer system, wherein each said close peer [[has]]includes one [[of]]or more neighbor peers (NP);

means for storing one identifier in memory for each of the one or more close peers, wherein the means for storing one identifier for each of the one or more close peers comprises a multilevel routing table cache (MRTC),

wherein each level in the MRTC includes a maximum number of entries,

wherein each level in the MRTC represents a segment of a number space corresponding to an identifier of the respective first and second means,

wherein the top level of the MRTC spans the entire number space,

wherein each successively lower level includes successively smaller spans,

wherein each said span in a level below the top level is a smaller segment than the entire number space,

wherein each said span is clustered around one said identifier of a corresponding said close peer, and

wherein the relative proximity between the close peers corresponds to the respective identifiers; [[and]]

means for storing an array for each said close peer, wherein:

each said array includes one [[of]] or more entries; and

each said entry:

corresponds to one said NP; and

includes an identifier for the NP;

wherein the first means is a close peer to the[[and]] second means ~~are close peers one to the other;~~

when the IP address of the first means changes ~~so as to cause~~ and there is
a break in an on[[]]going communication between the first and second means
for longer than a predetermined time threshold, each of the first and second
means further comprises:

means for addressing a message for transmission to each NP of
each close peer of the other of the first and second means for delivery of
the message thereto via each NP, wherein the message includes the
changed IP address thereof; and

means for:

receiving the message via the NP;

extracting the changed IP address of the other of the first and
second means from the message; and

resuming the on[[]]going communication using the changed
IP address of the other of the first and second means.

22. (Canceled)

23. (Currently Amended) The peer-to-peer system as defined
in Claim 21, wherein, when the IP address of either of the first and second
means ~~has changed~~ changes, said either of the first and second means
respectively further comprises:

means for addressing a message for transmission to each said NP when communication can[[]]not be made, after a predetermined threshold, to the corresponding said close peer, wherein the message includes the changed IP address; and

means for:

receiving the message;

extracting the changed IP address from the message; and

communicating with the corresponding said close peer using the changed IP address.

24. (Canceled)

25. (Original) The peer-to-peer system as defined in Claim 21, wherein each of the first and second means further comprises:

means for registering an identifier thereof with each of the close peers; and

means for receiving an identifier for each of the NP of each of the close peers.

26. (Canceled)

27. (Currently Amended) The peer-to-peer system as defined in Claim ~~[[26]]~~21, wherein for the first means, when a message is ~~to be~~ sent to a peer in the peer to peer system having an identifier not found in the MRTC of the first means, the first means further comprises:

means for forming a message for a destination said peer for which the identifier thereof is not found in the memory, wherein the message includes the identifier of the destination said peer; and

means for addressing the message to an intermediate said peer for which the identifier thereof~~[[:]]~~ is in the memory~~[[;]]~~ of the intermediate said peer, and is the proximally closest to the identifier of the destination said peer.

28. (Currently Amended) The peer-to-peer system as defined in Claim ~~[[27]]~~21, wherein the proximally closest said identifier of the intermediate said peer is found in a portion of the memory selected from the group consist of:

one said entry in one said array; and
the MRTC.

29. (Currently Amended) The peer-to-peer system as defined in Claim ~~[[27]]~~21, wherein:

the message ~~can be~~is delivered to the destination said peer from the first means by transmission via a number of said peers, wherein the number of said peers being not~~that is not~~ more than $O(\log_k N)$ in average;

k is ~~the~~ a factor by which the spans of each said successively lower level is successively smaller; and

N is ~~the~~ a number of identifiers in an identifier naming space for the MRTC.

30. (Original) The peer-to-peer system as defined in Claim 21, wherein each said peer is selected from the group consisting of:

a cellular telephone;

a computing device having a wired connection to the peer to peer system;

and

a computing device having a wireless connection to the peer to peer system.

31. – 43. (Canceled)